

EUROPEAN PATENT OFFICE

Patent Abstracts of Japan

PUBLICATION NUMBER : 08325713
PUBLICATION DATE : 10-12-96

APPLICATION DATE : 30-05-95
APPLICATION NUMBER : 07131322

APPLICANT : MATSUSHITA ELECTRIC WORKS LTD;

INVENTOR : HAYASHI TAKAO;

INT.CL. : C23C 14/20

TITLE : FORMATION OF METALLIC FILM ON ORGANIC SUBSTRATE SURFACE

ABSTRACT : PURPOSE: To attach a metallic film firmly to an org. substrate by irradiating the substrate surface with a light of wavelength activating bonding, further applying an amine soln. and then forming a metallic film by a vapor deposition method.

CONSTITUTION: The surface of an org. substrate is irradiated with a light having an energy equivalent to the binding energy of the substrate surface. The light activates the substrate surface to form a functional group such as -OH. The amine group of an amide soln. reacts with the functional group such as -OH to form an amide group. Since the amide group is highly reactive with the metal, the metallic film is firmly attached to the substrate surface. When the substrate surface is heat-treated or treated with plasma after the amine soln. is applied, the formation of the amide group is promoted more surely and preferably.

COPYRIGHT: (C) JPO

File 351:Derwent WPI 1963-2001/UD,UM &UP=200132

(c) 2001 Derwent Info Ltd

*File 351: Price changes as of 1/1/01. Please see HELP RATES 351.

72 Updates in 2001. Please see HELP NEWS 351 for details.

Set Items Description

--- -----

?e pn=de 19603746

Ref Items Index-term

E1	1	PN=DE 19603741
E2	1	PN=DE 19603742
E3	1	*PN=DE 19603746
E4	1	PN=DE 19603747
E5	1	PN=DE 19603748
E6	1	PN=DE 19603749
E7	1	PN=DE 1960375
E8	1	PN=DE 19603750
E9	1	PN=DE 19603751
E10	1	PN=DE 19603753
E11	1	PN=DE 19603754
E12	1	PN=DE 19603755

Enter P or PAGE for more

?s e3

S1 1 PN="DE 19603746"

?t s1/5/all

1/5/1

DIALOG(R)File 351:Derwent WPI

(c) 2001 Derwent Info Ltd. All rts. reserv.

011259504 **Image available**

WPI Acc No: 1997-237407/199722

XRPX Acc No: N97-196076

Electroluminescent device - has laminated encapsulation consisting of several layers

Patent Assignee: BOSCH GMBH ROBERT (BOSC)

Inventor: GROTHE W; HUEPPAUFF M; SCHMIDT C

Number of Countries: 020 Number of Patents: 002

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
-----------	------	------	-------------	------	------	------

DE 19603746	A1	19970424	DE 1003746	A	19960202	199722 B
-------------	----	----------	------------	---	----------	----------

WO 9716053	A1	19970501	WO 96DE1872	A	19960926	199723
------------	----	----------	-------------	---	----------	--------

Priority Applications (No Type Date): DE 1039050 A 19951020

Cited Patents: 1.Jnl.Ref; EP 326615; EP 350907; EP 372489; JP 7282975; US 5189405

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

DE 19603746 A1 7 H05B-033/04

WO 9716053 A1 G 19 H05B-033/04

Designated States (National): JP KR US

Designated States (Regional): AT BE CH DE DK ES FI FR GB GR IE IT LU MC NL PT SE

Abstract (Basic): DE 19603746 A

The electroluminescent lamination system (12) comprises a light emitting organic material between two electrodes connectable to a DC voltage source, and an encapsulation (28). The first electrode is a hole injection anode, while the second one is an electron injecting cathode.

The encapsulation consists of a laminated system (32), pref. with flexible layers (34, 36, 38), contg. a laminate geometry adapted to the electroluminescent laminate contour. The encapsulation laminate is typically deposited onto one side of the electroluminescent laminate, surrounding the electrodes (16, 18) and the organic material (14).

ADVANTAGE - Efficient protection against oxygen and water, and flexible configuration.

Dwg.1/3

Title Terms: ELECTROLUMINESCENT; DEVICE; LAMINATE; ENCAPSULATE; CONSIST; LAYER

Derwent Class: U14; X26

International Patent Class (Main): H05B-033/04

International Patent Class (Additional): H05B-033/12

File Segment: EPI

?logoff